



When Everything Counts!

Transaction Team™ 8810 *Interactive POS/Signature Capture Terminal*



Features

Exciting Design - Functional and ergonomic design with custom color options.

Hybrid Card Reader - The combined magnetic stripe and smart card reader enables one slot for the purchaser's card.

True Finger Touch - A light finger touch or tap of the stylus is all that is needed to activate the TT8810.

POS Communication - Abundant choices include RS-232, RS-485 (IBM Tailgate), PC USB, IBM USB, and 10/100 BaseT Ethernet for host terminal communications.

Advanced Data Router - Dynamically configure multi-port communications between USB, RS-232, Ethernet, and Aux RS-232. Manage multiple devices through one or more communications ports.

Ethernet Channel - Simultaneous communications to an Ethernet port off-loads high bandwidth transmissions. All POS commands are also available for "stand beside" operation.

Color or Monochrome LCD - Your choice of vibrant color or crisp monochrome LCD gives impact and excitement to the messages you want your customers to notice.

Security - EMV and Visa® PED compliant with a dedicated security processor, customer PINs are secured with industry standard encryption. Applications are authenticated with public key infrastructure (PKI).

Rugged - Designed and tested for the retail environment with a low cost, passive, tethered stylus, and screen protector.

HHP proudly introduces the revolutionary Transaction Team 8810 transaction terminal. Joining the HHP TT3101 and TT1500 family of products, this state-of-the-art terminal offers unrivaled power, versatility, and value.

POS payments, EBT, signature capture, and in-lane, targeted communications are enabled by the TT8810's fast processor and proven development environment.

The TT8810 comes standard with features that cost extra with other terminals. USB, 4MB Flash, 16 MB of RAM, and a 3-track magnetic stripe/smart card reader are standard. Choose a color LCD, additional memory, or 10/100 BaseT Ethernet factory options.

We know that the POS environment is tough on equipment. The TT8810 is drop tested to concrete and engineered to operate where other terminals cannot. The touch screen is protected by our patented, replaceable screen protection system that limits wear and blocks intrusion of water and dust.

Not another gray box, the innovative design is ergonomic, durable, and friendly to use. The TT8810 can be customized to your company's identity with logo and color options.

The HHP True Finger Touch with enhanced signature capture is intuitive and inviting. Customers can easily select buttons, key in PINs, and respond to prompts.

The TT8810 reads all three tracks from magnetic stripe cards and smart card chips in a single slot. The advanced hybrid card reader reduces training and confusion and speeds up transactions.

PIN's are protected with Master Session or DUKPT encryption. The exclusive HHP security indicator tells the customer when it is safe to enter their PIN.

To learn how the TT8810 can work for you, contact us at any of the locations listed on the back or visit us at www.hhp.com.

Upgrade your image.

Transaction Team 8810 Specifications

Display/Signature Window

Signature Window:	Resistive, transparent, pressure-sensitive touch screen
LCD Size:	4.45 x 3.3 in. (11.3 x 8.4 cm) (Active area)
LCD Resolution:	320 x 240 dot
Touch Pad Resolution:	903 x 1238 ppi

Communications

RS-232:	4800 to 115.2 Kbps
RS-232 Pass-Through:	Using Aux. Y cable with AC power adapter
RS-485:	Using 9A, 9B, 4B connectors (no power adapter)
PC USB:	AC power adapter required
IBM Retail USB:	SurePOS compatible (no power adapter)
Ethernet 10/100 BaseT:	Optional port. Cable not supplied.

Memory

Flash:	4MB
SRAM:	16MB

Dimensions (reference)

Width:	9.75 in. (24.8 cm)
Depth:	8.25 in. (21 cm)
Height:	2.95 in. (7.5 cm)
Weight:	2.4 lb. (1.1kg)

Power Requirements

Current Draw:	800 mA @ 12VDC
Source:	120V AC adapter

Optional Software Development Kit

Operating Systems:	Microsoft® Windows® 95, Windows® 98, Windows® 2000, Windows NT® 3.51 or higher, IBM 4680/4690 OS
Formats Supported:	BMP, CGM, DIB, EPS, MF, PCL, PCX, PLS, and TIF.
Object Tools:	Support for VBX and ActiveX OPOS and Java POS compliant

Signature Processing

Compression:	SIG - 5:1 (default), VBC - 4:1, NLC - 5:1, CMP - 10:1
Average File Size:	SIG - 1600 bytes, VBC - 500 bytes, NLC - 400 bytes, CMP - 200 bytes

Security

Hardware Features:	Secure key injection, tamper response, dedicated security processor
Firmware Authentication:	File authentication (SHA1 and RSA at 1024 bits)
Encryption:	PIN Encryption, Master/Session key, DUKPT, DES 64 and 128 bit

Approvals and Certifications

Agency Conformance:	FCC Class A, CE (LVD), UL 1950, CSA 22.2
----------------------------	--



Complies with EMC 89/336/EEC

IBM is a registered trademark of International Business Machines, Inc.

Microsoft® Windows® 95, Windows® 98, Windows® 2000, and Windows NT® are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.



When Everything Counts!

875 COTTING LANE, SUITE C
VACAVILLE, CA 95688
(800) 735-8560 [TEL] (707) 451-6418 [FAX]
WWW.LANDMARKIMAGE.COM
LANDMARK@LANDMARKIMAGE.COM